

759PPXCELFPress Brass Ball Valve

Specification Sheet

FEATURES & BENEFITS

- Lead Free Forged Brass
- F1960 PEX x Press
- 250 PSI (CWP)
- Max Temp. Rating: 250°F
- Full Port
- One O-Ring
- Blow Out Proof Stem
- Press Conforms to IAPMO PS117
- PEX Conforms to ASTM F1960
- cUPC, ANSI Z1157, NSF 14, NSF 372 & NSF 61 Approved
- Sizes 1/2" - 1"



DIMENSIONS

Part #	Size	DN	L	H	W	Cv
759PPXCE03LF	1/2"	0.591	3.46	1.81	2.95	18.55
759PPXCE04LF	3/4"	0.748	4.29	2.09	3.52	29.76
759PPXCE05LF	1"	0.984	4.29	2.25	4.07	51.55

MATERIAL SPECIFICATIONS

No.	Part	Material
1	Body	Lead Free Brass
2	Seat	PTFE
3	Ball	Stainless Steel
4	Packing	PTFE
5	Packing Nut	Brass
6	O-Ring	NBR
7	Handle Nut	Plated Steel
8	Lock Washer	Plated Steel
9	Handle	Plated Steel
10	Packing Nut	Brass
11	O-Ring	NBR
12	Cap	Lead Free Brass
13	Press O-Ring	EPDM

