

# 225FJR DI Flanged x MJ Valve - Open Right

## Specification Sheet

### FEATURES & BENEFITS

- Ductile Iron Gate Valve • AWWA C515-15
- Flanged x MJ • 300 PSI
- Open Right • Temp Range of 140°F - 180°F
- Resilient Wedge • UL Listed / FM Approved
- Non Rising Stem • AWWA C550 Epoxy
- NSF-61 / NSF-372 verified by UL Water Quality
- Flanges Conform to ANSI B16.1
- Mechanical Joint Outlet Complies with ANSI C153
- Can Be Fitted With Post Indicator Plate
- Sizes 4" – 12"

### MATERIAL SPECIFICATIONS

No.	Part	Material	ASTM Spec.
1	Body	Ductile Iron	A536 65-45-12
2	Disc	Ductile Iron EPDM Encapsulated	A536 65-45-12
3	Stem Nut	Bronze	B148 C95200
4	Stem	Stainless Steel	A276 Type 304SS
5	Gasket	Rubber	D2000 EPDM
6	Bolt	Stainless Steel	F93 Type304SS
7	Bonnet	Ductile Iron	A536 65-45-12
8	O-Ring	Rubber	D2000 EPDM
9	Thrust Collar	Bronze	B148 C95200
10	O-Ring	Rubber	D2000 EPDM
11	Gland	Ductile Iron	A536 65-45-12
12	O-Ring	Rubber	D2000 EPDM
13	Dust Ring	Rubber	D2000 EPDM
14	Operating Nut	Ductile Iron	A536 65-45-12
15	Bolts	Stainless Steel	F93 Type304SS
16	Washer	Stainless Steel	A276 Type 304SS
17	Handwheel	Ductile Iron	A536 65-45-12
18	Bolt	Stainless Steel	F93 Type304SS

### DIMENSIONS

Part #	Size	L	H	Do
225FJ11R	4"	9.5	11.8	10.0
225FJ13R	6"	11.0	16.4	12.0
225FJ14R	8"	12.0	20.7	14.0
225FJ15R	10"	13.9	24.5	16.0
225FJ16R	12"	14.5	28	16.0

